

ABSTRACT
Mobile Cellular Radio

A moveable switching system provides a cell, or small network of cells,
5 which moves with the aircraft or other vehicle on which it is located, but whose
operation appears to the user as an ordinary fixed base station of the "host" network
to which it is connected. A cellular mobile switching centre 16, on board the
aircraft, detects a call attempt or registration attempt from a mobile unit 10 and
generates a temporary onboard identity for association with the mobile identity code.
10 The temporary onboard identity code is associated with a node of the onboard part of
a satellite communications system. The code is returned to the onboard MSC 16
which sets up a call over a satellite system 13,6,3 to the MSC 41 of a host network
4.

When such a call is received from the satellite ground station 3 the host
15 MSC 41 routes the call to an interface unit 48 which retrieves the identities of the
cellular telephone and the onboard terminal. The cellular identity is passed to a
network registration unit 45 to allow a location update to allow calls to the cellular
telephone 10 to be routed to the mobile station 41. Consequently, any incoming calls
intended for the mobile user will now be directed to the network 4, as the mobile
20 user is currently registered there.

The interface unit 48 also passes the temporary onboard identity code to a
call diversion instruction unit 46, which generates a "divert on busy" instruction to
the VLR 44 (step 615). This causes any calls for the cellular telephone 10 received
by the host MSC 41 to be diverted via the satellite link 3, 6,13 to the node indicated
25 by the temporary onboard identity code, where the call is routed to the onboard MSC
16 and the code re-translated back to the cellular identity code to allow connection
to the cellular telephone 10.